



GENERAL INFORMATION

Magic Mask™ Professional Overspray Masking Liquid is a professional-quality masking liquid formulated to provide protection from paint overspray. Magic Mask traps loose dust and dirt for a cleaner paint job and will eliminate the need for costly car covers, wheel covers and bulky plastic sheeting.



1. PART NUMBER

- 36135 Magic Mask™ - Gallon
- 36136 Magic Mask™ - 5-Gallon Pail
- 36138 Magic Mask™ 55-Gallon Drum

2. PRODUCT USES

• Magic Mask™ protects against paint overspray from all solvent-based paints and coatings and light overspray from waterborne paints and coatings. Magic Mask™ is solvent resistant and safe for use on any OE or aftermarket paint, glass, fiberglass, vinyl, rubber, plastic or chrome. Apply on windshields, headlights, doors, grills, body panels, bumpers, tires, wheel wells, chassis, wheel covers, door jambs, engine compartments and vinyl tops.



3. MIXING

- Ready to Spray



4. SURFACE PREPARATION

- None; however, freshly waxed surfaces may require a second coat.



5. APPLICATION

- Spray Equipment: Stainless steel tip, needle and fluid passages are suggested.
- Siphon Feed: Pressure Pot:
 - 045 - .055 fluid tip
 - 40 - 50 psi gun pressure
 - 8 - 12 psi pot pressure
- Gravity Feed:
 - 1.2 - 1.4mm fluid tip
 - 35 - 40 psi at the gun
- HVLP:
 - .035 - .050 fluid tip
 - 4.5 - 5.0 psi at the air cap
- Dry Time: @77°F / 25 °C: 50% RH 20 - 25 minutes (medium coat with /5 - .7 mil dry film thickness)
- Baking: Multiple baking allowed. Maximum temperature: <160°F / 71°C



8. TECHNICAL INFORMATION

Coverage	350 - 400 sq ft/gal (at .5 - .7 mil dry film thickness)
Weight Per Full Gallon (Density)	8.6 +/- .25 lbs/gal
Viscosity @ 77°F	50 +/- 25 cps
Zahn #2 Cup	34 seconds
pH	7
Flashpoint	>200°F / 94°C Seta Flash Closed Cup
Volume Solids	Approximately 10%
VOC	0 grams/liter



9. HEALTH & SAFETY

• Read all warnings, first aid, and safety for all components before using. Keep out of reach of children and animals. Protect hands with impervious rubber gloves. Wear face, skin, and eye protection. When sanding, we recommend the use of a respiratory covering device to protect from dust (MSA mask P/N 459029 with MSA cartridge 464029 or equivalent). When using power equipment, refer to power tool manufacturer's recommendations for safety equipment. USC products are for industrial use by trained professionals only.

- Emergency Medical or Spill Control Information:
In U.S. and Canada call CHEMTREC at 1-800-424-9300

SPECIAL NOTE:

Avoid exposure to direct sunlight. Do not cover dried film (plastic sheeting, masking paper, etc.) Rinse with water from a hose or pressure washer within 48 hours of application. Areas with heavy overspray may need to be scrubbed. Removal works best when using a mitt or chamois while the surface is still wet.