

# MSDS

## SECTION 1 – Chemical Product and Company Identification

U S CHEMICAL & PLASTICS  
An Alco Industries Company  
600 Nova Drive SE  
Massillon, OH 44646  
PH 330-830-6000 - FAX 330-830-6005

For Chemical Emergency:  
CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666  
(For Canada call collect)

**PRODUCT NAME:** Kromate Lite  
**PRODUCT CODE:** (12036), 12050, 12060, 12065, 12073  
12080, 12081, 12082  
**SYNONYM/CROSS REFERENCE:** Polyester Paste  
**SCHEDULE B NUMBER:** 3214.10.0090

## SECTION 2 – Hazard Identification

OVEREXPOSURE EFFECTS:

ACUTE EFFECTS:

EYES: Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

SKIN: Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed through the skin.

INHALATION: Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal.

INGESTION: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

PRIMARY ROUTES OF EXPOSURE: skin, inhalation, eyes

## SECTION 3 – Composition, Information or Ingredients

<u>INGREDIENTS</u>	<u>WGT%</u>	<u>CAS #</u>
Styrene	10-20%	100-42-5
Non-fibrous Talc	35-45%	14807-96-6
Calcium Carbonate	1-10%	1317-65-3, 471-34-1
Glass Beads	1-10%	1344-09-8, 7775-19-1
Silicon Dioxide Amorphous	1-5%	7631-86-9

# MSDS

## **SECTION 4 – First Aid Measures**

**INHALATION:** If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

**SKIN:** For skin contact, wash promptly with soap and excess water.

**EYES:** For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

**INGESTION:** If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

## **SECTION 5 – Fire-Fighting Measures**

**FLASH POINT:** 105°F/40°C Seta Flash Closed cup

**LOWER FLAMMABLE LIMIT %:** N/E

**UPPER FLAMMABLE LIMIT %:** N/E

**FIRE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**SPECIAL FIRE FIGHTING PROCEDURES:** Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** Closed containers exposed to high temperatures, such as fire conditions may rupture.

## **SECTION 6 – Accidental Release Measures**

**SPILLS, LEAK OR RELEASE:** Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent.

## **SECTION 7 – Handling and Storage**

**STORAGE AND HANDLING:** Use with adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

## **SECTION 8 – Exposure Controls and Personal Protection**

<b><u>INGREDIENTS</u></b>	<b><u>CAS #</u></b>	<b><u>TLV/PEL</u></b>
Styrene	100-42-5	ACGIH TLV 20 ppm STEL 100 ppm OSHA PEL 100 ppm CPEL 200 ppm (See Health Hazard Information)
Non-fibrous Talc	14807-96-6	ACGIH TWA 2 mg/m <sup>3</sup> TLV 20 mppcf
Calcium Carbonate	1317-65-3, 471-34-1	ACGIH TWA 10 mg/m <sup>3</sup>
Glass Beads	1344-09-8, 7775-19-1	ACGIH TWA 10 mg/m <sup>3</sup>
Silicon Dioxide Amorphous	7631-86-9	OSHA PEL 15 mg/m <sup>3</sup>

# MSDS

RESPIRATORY PROTECTION: If component TLV limits are exceeded, use NIOSH/MSHA approved respirator to remove vapors. Use an air-supplied respirator if necessary.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

## **SECTION 9 – Physical and Chemical Properties**

APPEARANCE: Yellow smooth paste

SPECIFIC GRAVITY: 1.16

VAPOR PRESSURE (mmHG): Heavier than air

BOILING POINT: N/A<sub>v</sub>

VAPOR DENSITY: Heavier than air

EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether

VOLATILES BY WEIGHT: 13-20%

SOLUBILITY IN WATER: None

VOC: Grams/liter = less exempts 212; unconsumed VOC upon curing 0.8

## **SECTION 10 – Stability and Reactivity**

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, and Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

## **SECTION 11 – Toxicological Information**

### **CHRONIC EFFECTS:**

Overexposure to this material has apparently been known to cause the following effects in lab animals: Eye, skin, lung, and central nervous system damage.

CARCINOGEN: YES  NO

TERATOGEN: YES  NO

MUTAGEN: YES  NO

### **STYRENE CARCINOGENICITY**

Styrene is listed by IARC to be a possible carcinogen. Styrene studies have shown that Styrene causes cancer in certain laboratory animals. However, there is insufficient evidence to conclude that Styrene is a human carcinogen.

## **SECTION 12 – Ecological Information**

N/E

# MSDS

## SECTION 13 – Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

## SECTION 14 – Transport Information

### **For Ground Transport: In USA**

Consumer Commodity ORM-D

### **For Air Transport:**

Must be re-boxed to UN specified packaging in quantities of no more than 5 kg per fiberboard box

UN3269, Polyester Resin Kit, 3, PGIII

Packing Instruction 312

### **For Ocean Transport:**

UN3269, Polyester Resin Kit, 3, PGIII, F/P 40°C

EMS # F-E, S-D, In limited quantity

## SECTION 15 – Regulatory Information

CALIFORNIA PROPOSITION 65:

Trace amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be present in this product.

### SECTION 313 SUPPLIER NOTIFICATION:

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CHEMICAL NAME</u>	<u>CAS</u>	<u>% BY WGT</u>
Styrene	100-42-5	10-20%

This information must be included in all MSDS that are copied and distributed for this chemical.

## SECTION 16 – Other Information

HMIS RATING:	Health	2	4 = Extreme
	Fire	2	3 = High
	Reactivity	1	2 = Moderate
			1 = Slight
			0 = Insignificant

Personal Protection - See Section VIII

# MSDS

## ABBREVIATIONS

IARC	= International Agency for Research on Cancer
ACGIH	= American Conference of Governmental Industrial Hygienists
NIOSH	= National Institute of Occupational Safety and Health
TLV	= Threshold Limit Value
PEL	= Permissible Emission Level
DOT	= Department of Transportation
NTP	= National Toxicology Program
N/AV	= Not Available
N/AP	= Not Applicable
N/E	= Not Established
N/D	= Not Determined

PREPARED BY: U S CHEMICAL & PLASTICS  
An Alco Industries Company  
600 NOVA DRIVE SE  
MASSILLON, OH 44646

TELEPHONE NBR: 330-830-6000  
FAX NBR: 330-830-6005

DATE REVIEWED: November 3, 2009  
DATE REVISED: November 3, 2009  
REVISION: Sections 6, 12, 14

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.