

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 1K SELF ETCH WELD-THRU PRIMER BEIGE  
MSDS Number : 888100004239  
Product Use Description : Solvent-borne coatings, Primers  
Company : Peter Kwasny Inc.  
510 Broadhollow Road 209  
Melville-NY, 11747  
Telephone : 001-727-363-3047  
Telefax : 001-727-363-0630  
Emergency telephone : 001-352-323-3500  
number

## SECTION 2. HAZARDS IDENTIFICATION

### Emergency Overview

**Regulatory status** : This product, material or substance is a WHMIS controlled product per Sections 33 - 66, Part IV of the CPR.

Signal Word : DANGER  
Form : aerosol  
Odour : characteristic  
Odour - Control parameters : no data available  
Hazard Summary : Flammable Aerosol  
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C / 122 °F.  
May cause fire.  
May cause cancer.  
  
Irritant  
Sensitizer

### Potential Health Effects

Eyes : Causes eye irritation.  
Skin : May cause skin irritation.  
May cause allergic skin reaction.  
Inhalation : Causes respiratory tract irritation.  
May cause allergic respiratory reaction.  
Chronic Exposure : Repeated absorption may result in bladder tumors.

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



Target Organs : Central nervous system  
Eyes  
Skin

Carcinogenicity:

ACGIH : ethylbenzene (CAS-No.: 100-41-4)

NTP : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC : Titanium oxide (TiO<sub>2</sub>) (CAS-No.: 13463-67-7)  
Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (CAS-No.: 14807-96-6)  
ethylbenzene (CAS-No.: 100-41-4)

OSHA : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65 : WARNING! This product contains a chemical known in the State of California to cause cancer.  
ethylbenzene (CAS-No.: 100-41-4)

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
acetone; propan-2-one; propanone	67-64-1	>= 25 - < 35
butan-1-ol; n-butanol	71-36-3	>= 10 - < 12.5
propane	74-98-6	>= 10 - < 12.5
n-butyl acetate	123-86-4	>= 7 - < 10
butane	106-97-8	>= 7 - < 10
xylene	1330-20-7	>= 3 - < 5
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	>= 3 - < 5
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecularweight 700-1200)	25068-38-6	>= 2 - < 3
2-methoxy-1-methylethyl acetate	108-65-6	>= 1.5 - < 2
ethylbenzene	100-41-4	>= 1 - < 1.5

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area. Never give anything by mouth to an unconscious person. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). When symptoms persist or in all cases of doubt seek medical advice. Take off all contaminated clothing immediately.
- Inhalation : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
- Skin contact : Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners.
- Eye contact : Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
- Ingestion : If a person vomits when lying on his back, place him in the recovery position. Clean mouth with water and drink afterwards plenty of water. Ingest activated charcoal. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5. FIRE-FIGHTING MEASURES

- Form : aerosol
- Flash point : < 0 °C (< 32 °F)
- Ignition temperature : 365 °C (689 °F)
- Lower explosion limit : 1.4 %(V)
- Upper explosion limit : 8.5 %(V)
- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Extinguishing media which must not be used for safety reasons : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Do not use a solid water stream as it may scatter and spread fire.

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



- 
- Special protective equipment for fire-fighters : Use personal protective equipment.  
Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Use water spray to cool unopened containers.  
Exposure to decomposition products may be a hazard to health.  
Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- 

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Ventilate the area.  
Remove all sources of ignition.  
Avoid inhalation of vapour or mist.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Should not be released into the environment.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.
- 

## SECTION 7. HANDLING AND STORAGE

### Handling

- Handling : Do not breathe vapours or spray mist.  
Avoid contact with skin and eyes.  
Take precautionary measures against static discharges.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
Limit the stocks at work place.  
Do not spray on a naked flame or any other incandescent material.
-

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



Use only in well-ventilated areas.  
For personal protection see section 8.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.  
Do not smoke.  
Vapours may form explosive mixtures with air.  
Vapours are heavier than air and may spread along floors.  
Electrical equipment should be protected to the appropriate standard.

Dust explosion class : not applicable

## Storage

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C / 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Please observe the storage instructions for aerosols

Advice on common storage : Keep away from food, drink and animal feedingstuffs.  
Keep away from oxidising agents and strongly acid or alkaline materials.

Storage period : 24 Months

Storage temperature : 5 - 30 °C (41 - 86 °F)

Other data : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Components	CAS-No.	List	Type:	Value
acetone; propan-2-one; propanone	67-64-1	OEL (QUE)	TWA	750 ppm 1,780 mg/m3
		OEL (QUE)	STEL	1,000 ppm 2,380 mg/m3
		CAD AB OEL	TWA	750 ppm 1,800 mg/m3
		CAD AB OEL	STEL	1,000 ppm 2,400 mg/m3
		CAD BC OEL	TWA	250 ppm
		CAD BC OEL	STEL	500 ppm

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



		CAD ON OEL	TWA	500 ppm
		CAD ON OEL	STEL	750 ppm
butan-1-ol; n-butanol	71-36-3	OEL (QUE)	CEILING	50 ppm 152 mg/m3
		CAD AB OEL	CEILING	50 ppm 152 mg/m3
		CAD BC OEL	TWA	15 ppm
		CAD BC OEL	CEILING	30 ppm
		CAD ON OEL	TWA	20 ppm
propane	74-98-6	OEL (QUE)	TWA	1,000 ppm 1,800 mg/m3
		CAD AB OEL	TWA	1,000 ppm 1,800 mg/m3
		CAD AB OEL	STEL	1,500 ppm 2,700 mg/m3
		CAD BC OEL	TWA	1,000 ppm
		CAD ON OEL	TWA	1,000 ppm
n-butyl acetate	123-86-4	OEL (QUE)	TWA	150 ppm 713 mg/m3
		OEL (QUE)	STEL	200 ppm 950 mg/m3
		CAD AB OEL	TWA	150 ppm 713 mg/m3
		CAD AB OEL	STEL	200 ppm 950 mg/m3
		CAD BC OEL	TWA	20 ppm
		CAD ON OEL	TWA	150 ppm 710 mg/m3
		CAD ON OEL	STEL	200 ppm 950 mg/m3
Titanium oxide (TiO2)	13463-67-7	CAD BC OEL	TWA	3 mg/m3
		CAD BC OEL	TWA	10 mg/m3
butane	106-97-8	CAD AB OEL	TWA	800 ppm 1,900 mg/m3
		CAD BC OEL	TWA	600 ppm
		CAD BC OEL	STEL	750 ppm
		OEL (QUE)	TWA	800 ppm 1,900 mg/m3
		CAD ON OEL	TWA	800 ppm 1,900 mg/m3
xylene	1330-20-7	OEL (QUE)	TWA	100 ppm 434 mg/m3
		OEL (QUE)	STEL	150 ppm 651 mg/m3
		CAD AB OEL	TWA	100 ppm 434 mg/m3
		CAD AB OEL	STEL	150 ppm 651 mg/m3
		CAD BC OEL	TWA	100 ppm
		CAD BC OEL	TWA	0.5 ppm
		CAD BC OEL	STEL	150 ppm
		CAD ON OEL	TWA	100 ppm 435 mg/m3
		CAD ON OEL	STEL	150 ppm 650 mg/m3
Talc (Mg3H2(SiO3)4)	14807-96-6	OEL (QUE)	TWA	3 mg/m3
		CAD AB OEL	TWA	2 mg/m3
		CAD BC OEL	TWA	2 mg/m3
		CAD ON OEL	TWA	2 mg/m3
		CAD ON OEL	TWA	2
2-methoxy-1-methylethyl acetate	108-65-6	CAD BC OEL	TWA	50 ppm
		CAD BC OEL	STEL	75 ppm
		CAD ON OEL	TWA	50 ppm 270 mg/m3
ethylbenzene	100-41-4	OEL (QUE)	TWA	100 ppm 434 mg/m3
		OEL (QUE)	STEL	125 ppm 543 mg/m3
		CAD AB OEL	TWA	100 ppm 434 mg/m3
		CAD AB OEL	STEL	125 ppm 543 mg/m3
		CAD BC OEL	TWA	100 ppm
		CAD BC OEL	STEL	125 ppm
		CAD ON OEL	TWA	100 ppm 435 mg/m3
		CAD ON OEL	STEL	125 ppm 540 mg/m3
Diiron trioxide	1309-37-1	OEL (QUE)	TWA	10 mg/m3

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



		CAD BC OEL	TWA	3 mg/m3
		CAD BC OEL	TWA	10 mg/m3
		CAD ON OEL	TWA	5 mg/m3

- Engineering measures : Provide adequate ventilation.
- Eye protection : Safety glasses
- Hand protection : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.  
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.
- Skin and body protection : impervious clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
respirator with ABEK filter
- Hygiene measures : Do not inhale aerosol.  
When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and at the end of workday.  
Wash contaminated clothing before re-use.  
Handle in accordance with good industrial hygiene and safety practice.  
General industrial hygiene practice.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : aerosol
- Odour : characteristic
- Flash point : < 0 °C (< 32 °F)
- Ignition temperature : 365 °C (689 °F)
- Thermal decomposition : Heating can release hazardous gases., Fire or intense heat may cause violent rupture of packages.
- Lower explosion limit : 1.4 %(V)

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



---

Upper explosion limit	: 8.5 %(V)
Vapour pressure	: 3.6 hPa at 20 °C (68 °F)
Density	: 0.85 g/cm <sup>3</sup> at ca.20 °C (68 °F)
Volatile organic compounds (VOC) content	: 49.95 %

---

## SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Strong acids and strong bases Oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), dense black smoke.
Thermal decomposition	: Heating can release hazardous gases. Fire or intense heat may cause violent rupture of packages.
Hazardous reactions	: Vapours may form explosive mixture with air. Note: No decomposition if used as directed.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity	: Irritating to respiratory system.
Skin irritation	: Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin.
Eye irritation	: The liquid splashed in the eyes may cause irritation and reversible damage. Strong lachrymation can make it difficult to escape
Carcinogenicity	: No data is available on the product itself.
Toxicity to reproduction	: No data is available on the product itself.
Teratogenicity	: No data is available on the product itself.
Further information	: Symptoms of overexposure may be headache, dizziness,

---

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



tiredness, nausea and vomiting.  
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.  
Liver and kidney injuries may occur.  
Even the smallest quantities that enter into the lung due to swallowing or subsequent vomiting can lead to a pulmonary oedema or pneumonia.

## Component:

acetone; propan-2-one; propanone 67-64-1

Acute oral toxicity: LD50 rat  
Dose: 5,800 mg/kg

Acute dermal toxicity: LD50 rabbit  
Dose: 20,000 mg/kg

Acute inhalation toxicity: LC50 rat  
Dose: 70 mg/l  
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Mild skin irritation  
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin.

Eye irritation: Classification: Irritating to eyes.  
Result: Moderate eye irritation

butan-1-ol; n-butanol 71-36-3

Acute oral toxicity: LD50 rat  
Dose: 790 mg/kg

Acute dermal toxicity: LD50 rabbit  
Dose: 3,400 mg/kg

Acute inhalation toxicity: LC50 rat  
Dose: > 18 mg/l  
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Risk of serious damage to eyes.

propane 74-98-6

Skin irritation: Classification: Irritating to skin.  
Result: Skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Mild eye irritation

n-butyl acetate 123-86-4

Acute oral toxicity: LD50 rat  
Dose: 13,100 mg/kg

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



		<p><u>Acute dermal toxicity</u>: LD50 rabbit Dose: &gt; 14,100 mg/kg</p> <p><u>Acute inhalation toxicity</u>: LC50 rat Dose: 21 mg/l Exposure time: 4 h</p> <p><u>Skin irritation</u>: Result: Mild skin irritation</p> <p><u>Eye irritation</u>: Result: Mild eye irritation</p>
xylene	1330-20-7	<p><u>Acute oral toxicity</u>: LD50 rat Dose: 2,840 mg/kg</p> <p><u>Acute dermal toxicity</u>: LD50 rabbit Dose: ca. 4,500 mg/kg</p> <p><u>Acute inhalation toxicity</u>: LC50 rat Dose: 6,350 mg/l Exposure time: 4 h</p> <p><u>Skin irritation</u>: Classification: Irritating to skin. Result: Mild skin irritation Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.</p> <p><u>Eye irritation</u>: Classification: Irritating to eyes. Result: Mild eye irritation</p>
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	<p><u>Skin irritation</u>: Classification: Irritating to skin. Result: Mild skin irritation</p>
reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecularweight 700-1200)	25068-38-6	<p><u>Skin irritation</u>: Classification: Irritating to skin. Result: Mild skin irritation Prolonged skin contact may cause skin irritation and/or dermatitis.</p> <p><u>Sensitization</u>: May cause sensitization by skin contact.</p>
2-methoxy-1-methylethyl acetate	108-65-6	<p><u>Acute oral toxicity</u>: LD50 mouse Dose: 8,532 mg/kg</p> <p><u>Acute dermal toxicity</u>: LD50 rabbit Dose: 7,500 mg/kg</p> <p><u>Eye irritation</u>: Classification: Irritating to eyes. Result: Mild eye irritation</p>
ethylbenzene	100-41-4	<p><u>Acute oral toxicity</u>: LD50 rat Dose: 3,500 mg/kg</p> <p><u>Acute dermal toxicity</u>: LD50 rabbit Dose: 15,500 mg/kg</p>

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



Acute inhalation toxicity: LC50 rat  
Dose: 18 mg/l  
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.  
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Risk of serious damage to eyes.

## SECTION 12. ECOLOGICAL INFORMATION

Adsorbed organic bound halogens (AOX) : not included  
Volatile organic compounds (VOC) content : 49.95 %  
Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

## SECTION 13. DISPOSAL CONSIDERATIONS

Adequate disposal : In accordance with local and national regulations.  
Please ensure aerosol cans are sprayed completely empty (including propellant)  
Containers that have not been emptied in compliance with regulations are regarded as hazardous waste.

## SECTION 14. TRANSPORT INFORMATION

### DOT 49 CFR

Proper shipping name : AEROSOLS  
UN-No. : 1950  
Class : 2.1  
Packing group :  
Emergency Response : 126  
Guidebook Number

### TDGR

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



Proper shipping name : AEROSOLS  
UN-No. : 1950  
Class : 2.1  
Packing group :  
Emergency Response : 126  
Guidebook Number

## ICAO / IATA-DGR

UN UN-No. : 1950  
Description of the goods : AEROSOLS  
Class : 2.1  
ICAO-Labels : 2.1  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203  
Packing instruction (passenger aircraft) : Y203

## IMDG-Code

UN-No. : UN 1950  
Description of the goods : AEROSOLS  
Class : 2.1  
IMDG-Labels : 2.1  
EmS Number : F-D S-U  
Marine pollutant : no

## SECTION 15. REGULATORY INFORMATION

**TSCA Status** : On TSCA Inventory

**DSL Status** : All components of this product are on the Canadian DSL list.

**California Prop. 65** : WARNING! This product contains a chemical known in the State of California to cause cancer.

ethylbenzene 100-41-4

**WHMIS Classification** : B5 Flammable Aerosol  
Flammable Aerosol

D2A Very Toxic Material Causing Other Toxic Effects

# Material Safety Data Sheet

Print Date: 02/13/2007

Revision Date : 02/13/2007

Trade name: **1K SELF ETCH WELD-THRU PRIMER BEIGE**

Part number:  
3 680 002

Version : 2.1



---

D2B Toxic Material Causing Other Toxic Effects  
Carcinogen  
Moderate skin irritant  
Moderate respiratory irritant  
Severe eye irritant  
Skin sensitizer

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

---

## SECTION 16. OTHER INFORMATION

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by : TechniData BCS GmbH  
Birlenbacher Str. 19  
D-57078 Siegen  
Germany  
Telephone: +49-(0)271-88072-0  
Revision Date : 02/13/2007