

MSDS

SECTION 1 – Chemical Product and Company Identification

MORTON PAINT COMPANY
U S CHEMICAL & PLASTICS
An Alco Industries Company
600 Nova Drive SE
Massillon, OH 44646
PH 330-830-6000 - FAX 330-830-6005

For Chemical Emergency:
CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666
(For Canada call collect)

PRODUCT NAME: Defender Truck Bed Liner Activator Part B
VOC COMPLIANT
PRODUCT CODE: (997506), 1600-2, 1635-4
SYNONYM/CROSS REFERENCE: Part B of Two-Part Paint
SCHEDULE B NUMBER: 3208.20.0000

SECTION 2 – Hazard Identification

OVEREXPOSURE EFFECTS:

ACUTE EFFECTS:

EYES: Severe irritant. Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

SKIN: Severe irritant. Contact with skin can cause irritation, (minor itching, burning and/or redness), dermatitis, defatting may be readily absorbed through the skin.

INHALATION: Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal. May be toxic.

INGESTION: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

PRIMARY ROUTES OF EXPOSURE: Inhalation, skin, eyes

SECTION 3 – Composition, Information or Ingredients

<u>INGREDIENTS</u>	<u>WGT%</u>	<u>CAS #</u>
Xylene	10-20%	1330-20-7
Polyamide Resin	40-50%	68410-23-1
Toluene	15-25%	108-88-3
(Dimethylamino) Methylphenol	1-5%	25338-55-0
Phenol	1-3%	108-95-2
Ethyl benzene	1-5%	100-41-4
Triethylene Tetramine (TETA)	1-3%	112-24-3
Nonyl Phenol (reactive diluents)	1-10%	84852-15-3

SECTION 4 – First Aid Measures

INHALATION: If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

SKIN: For skin contact, wash promptly with soap and excess water. Consult a physician if irritation persists.

EYES: For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

INGESTION: If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

MSDS

SECTION 5 – Fire-Fighting Measures

FIRE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES: Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers exposed to high temperatures, such as fire conditions may rupture.

SECTION 6 – Accidental Release Measures

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent.

SECTION 7 – Handling and Storage

STORAGE AND HANDLING: Use with adequate ventilation. Harmful or fatal if swallowed. Avoid contact with eyes and skin. Avoid breathing vapors. Flammable. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

SECTION 8 – Exposure Controls and Personal Protection

<u>INGREDIENTS</u>	<u>CAS #</u>	<u>TLV/PEL</u>
Xylene	1330-20-7	TLV: 100 ppm, STEL: 150 ppm
Polyamide Resin	68410-23-1	N/E Corrosive to skin
Toluene	108-88-3	ACGIH TLV: 50 ppm skin OSHA TLV: 100 ppm, STEL: 150 ppm
(Dimethylamino) Methylphenol	25338-55-0	N/E Corrosive to skin
Phenol	108-95-2	TLV: 5 ppm skin
Ethyl benzene	100-41-4	TLV:PEL: 100 ppm
Triethylene Tetramine (TETA)	112-24-3	AIHA (WEEL): 1 ppm
Nonyl Phenol (reactive diluents)	84852-15-3	N/E

RESPIRATORY PROTECTION: If component exposure limits are exceeded, use NIOSH/MSHA approved air purifying or fresh air supplied respirator to remove vapors. Use an air-supplied respirator if necessary.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

SECTION 9 – Physical and Chemical Properties

FLASH POINT: 45°F/7°C Seta Flash Closed cup

LOWER FLAMMABLE LIMIT %: N/E

UPPER FLAMMABLE LIMIT %: N/E

APPEARANCE: Amber liquid, solvent odor

SPECIFIC GRAVITY: 0.92

VAPOR PRESSURE (mmHG): N/E

BOILING POINT: N/E

MSDS

VAPOR DENSITY: Heavier than air
EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether
VOLATILES BY WEIGHT: Approximately 52%
SOLUBILITY IN WATER: Slight
VOC (less water & exempts): 395 g/l; 3.3 lbs/gal as packaged
As mixed with 1600 Resin – Part A: 310 g/l; 2.6 lbs/gal

SECTION 10 – Stability and Reactivity

STABILITY: Stable
CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.
INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, and Carbon.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 – Toxicological Information

CHRONIC EFFECTS:

Overexposure to this material has apparently been known to cause the following effects in lab animals:
Anemia, liver abnormalities, kidney, eye, skin, lungs, blood, sensitization, reproductive effects, and central nervous system damage.

CARCINOGEN: YES NO
TERATOGEN: YES NO
MUTAGEN: YES NO

TOLUENE STATEMENT (API STUDY, 1986)

Prolonged breathing of 2,000 ppm Toluene by pregnant rats was toxic to their fetuses (reduced body weight, delayed ossification, skeletal variations, but was not teratogenic).

SECTION 12 – Ecological Information

N/E

SECTION 13 – Disposal Considerations

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

SECTION 14 – Transport Information

For Ground Transport: In USA

Consumer Commodity ORM-D in cases with inner containers 1 gallon or less.

For Air Transport:

Must be re-boxed to UN specified packaging.
UN1263, Paint, 3, PG II
Packing Instruction 309, 310

MSDS

For Ocean Transport:

With inner containers of 5L or less:

UN1263, Paint, 3, PG II, F/P 7C

EMS # F-E, S-E

In limited quantity

SECTION 15 – Regulatory Information

CALIFORNIA PROPOSITION 65:

This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

SECTION 313 SUPPLIER NOTIFICATION:

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CHEMICAL NAME</u>	<u>CAS</u>	<u>% BY WGT</u>
Xylene	1330-20-8	10-20%
Ethyl Benzene	100-41-4	1-5%
Phenol	108-95-2	1-3%
Toluene	108-88-3	15-25%

This information must be included in all MSDS that are copied and distributed for this chemical.

DO NOT FLAME CUT, WELD OR MELT EMPTY CONTAINERS.

SECTION 16 – Other Information

HMIS RATING:	Health	2	4 = Extreme
	Fire	3	3 = High
	Reactivity	0	2 = Moderate
			1 = Slight
			0 = Insignificant

Personal Protection - See Section VIII

ABBREVIATIONS

IARC	= International Agency for Research on Cancer
ACGIH	= American Conference of Governmental Industrial Hygienists
NIOSH	= National Institute of Occupational Safety and Health
TLV	= Threshold Limit Value
PEL	= Permissible Emission Level
DOT	= Department of Transportation
NTP	= National Toxicology Program
N/AV	= Not Available
N/AP	= Not Applicable
N/E	= Not Established
N/D	= Not Determined

MSDS

PREPARED BY: U S CHEMICAL & PLASTICS
An Alco Industries Company
600 NOVA DRIVE SE
MASSILLON, OH 44646

TELEPHONE NBR: 330-830-6000
FAX NBR: 330-830-6005

DATE REVIEWED: August 26, 2010
DATE REVISED: August 26, 2010
REVISION: New Format

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.