

Page 1 of 4 Bulk, Impact Flexible – Guide Coat Sandable Primer Surfacer - Black
MATERIAL SAFETY DATA SHEET

MORTON PAINT COMPANY
US Chemical & Plastics
Alco Industries Companies
600 Nova Dr SE
Massillon, OH 44646
Phone (330) 830-6000 Fax: (330) 830-6005

FOR CHEMICAL EMERGENCY SPILL, LEAK, FIRE
EXPOSURE OR ACCIDENT, CALL DAY OR NIGHT
IN USA: CHEMTREC 1-800-424-9300
FOR CANADA CALL COLLECT
CANUTEC 1-613-996-6666

=====

SECTION I - IDENTIFICATION OF PRODUCT

=====

PRODUCT NAME: Impact Flexible Primer/Surfacer - Satin Black
SYNONYM OR CROSS REFERENCE: Acrylic Lacquer Primer
PRODUCT CODE: (999030), 201-1, 201-4, 201-5, 214 Bulk
PROPER SHIPPING NAME: Paint, Flammable Liquid, UN1263

=====

SECTION II - HAZARDOUS INGREDIENTS

=====

INGREDIENTS	WEIGHT %	CAS NUMBER	TLV/PEL
Proprietary Synthetic Resins	15-20%	N/Av	N/E
Carbon Black	1-5%	1333-86-4	TLV: 3 mg/m ³
Talc (Non-asbestos Type)	10-20%	14807-96-6	TLV: 2 mg/m ³
Toluene	20-30%	108-88-3	PEL: 100 ppm
PM Acetate	5-10%	108-65-6	N/E
Methyl Ethyl Ketone	15-20%	78-93-3	PEL: 200 ppm
Isobutyl Acetate	10-15%	110-19-0	PEL: 150 ppm

=====

SECTION III - PHYSICAL DATA

=====

APPEARANCE: Black Liquid
SPECIFIC GRAVITY: 1.07
VAPOR PRESSURE (mmHg): N/Av
BOILING POINT: N/Av
MELTING POINT: N/Av

VAPOR DENSITY: Heavier than air
EVAPORATION RATE: (Diethyl Ether = 1)
Slower than Diethyl Ether
VOLATILES BY WEIGHT: Approx. 61%
SOLUBILITY IN WATER: Insoluble
VOC (less water and exempts): 620 Grams/Liter 5.20 lbs/g;

=====
SECTION IV - FIRE AND EXPLOSION DATA
=====

FLASH POINT: 45°F/7°C Seta Flash Closed Cup

LOWER FLAMMABLE LIMIT %: N/E

UPPER FLAMMABLE LIMIT %: N/E

FIRE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam.

SPECIAL FIRE FIGHTING PROCEDURES: Fight like a fuel oil fire. Cool fire exposed containers with water spray. Fire Fighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: (Conditions of Flammability) Combustible. Closed containers exposed to high temperatures, such as fire conditions may rupture.

=====
SECTION V - HEALTH HAZARD/TOXICOLOGICAL PROPERTIES
=====

OVEREXPOSURE EFFECTS:

ACUTE EFFECTS:

EYES - Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

SKIN - Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed through the skin.

INHALATION - Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal. May be toxic.

INGESTION - Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

CHRONIC EFFECTS:

Overexposure to this material has apparently been known to cause the following effects in lab animals: anemia, kidney, lung, brain, eye, cardiac, liver damage

CARCINOGENIC __ YES X NO

TERATOGEN __ YES X NO

MUTAGEN __ YES X NO

TOLUENE STATEMENT (API STUDY, 1986) Prolonged breathing of 2,000 ppm Toluene by pregnant rats was toxic to their fetuses (reduced body weight, delayed ossification, skeletal variation), but was not teratogenic.

ROUTES OF EXPOSURE: Skin contact, inhalation

FIRST AID:

INHALATION -If inhaled, remove victim from exposure to well ventilated area. Make him/her comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

SKIN - For skin contact, wash promptly with soap and excess water. Consult a physician.

EYES - For eye contact, flush promptly with excess water. Consult a physician.

INGESTION - If ingested, do not induce vomiting. Call a physician immediately.

=====
SECTION VI - REACTIVITY DATA
=====

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Unknown other than Carbon Dioxide, Carbon Monoxide and Carbon

HAZARDOUS POLYMERIZATION: Will not occur.

=====

SECTION VII - SPILL AND DISPOSAL PROCEDURE

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent and clean up with spark-proof tools.

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

=====

SECTION VIII - PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C chemical/mechanical type filter system to remove a combination of particles, gas, and vapors. Use an air supplied respirator if necessary.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels and flammable limits in air below the level necessary to product explosion or fire. General mechanical ventilation should comply with OSHA 1910.94.

PROTECTIVE GLOVES: To prevent prolonged exposure, use rubber gloves, solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

=====

SECTION IX - HANDLING AND STORAGE PRECAUTIONS

STORAGE AND HANDLING: Use with adequate ventilation. Harmful or fatal if swallowed! Extremely flammable. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis and oxidizers.

=====

SECTION X - ADDITIONAL INFORMATION

SHIPPING INFORMATION: Please comply with DOT regulations in USA

HMIS RATING:	Health	<u>2</u>	4 = Extreme
	Fire	<u>3</u>	3 = High
	Reactivity	<u>1</u>	2 = Moderate
	Personal Protection	- See Section VIII	1 = Slight
			0 = Insignificant

=====

CALIFORNIA PROPOSITION 65:

WARNING: This product contains Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

SECTION 313 SUPPLIER NOTIFICATION:

Chemical Name	CAS Number	Weight Percentage
Toluene	108-88-3	20-30%

This information must be included on all MSDS that are copied or distributed.

ABBREVIATIONS:

IARC =	International Agency for Research on Cancer	N/AV =	Not Available
ACGIH =	American Conference of Governmental Industrial Hygienists	N/AP =	Not Applicable
NIOSH =	National Institute of Occupational Safety and Health	N/E =	Not Established
DOT =	Department of Transportation	NTP =	National Toxicology Program
TLV =	Threshold Limit Value	PEL =	Permissible Emission Level

REFERENCES

1. ACGIH. Threshold Limit Values and Biological Exposure Indices for 1988-89
2. Material Safety Data Sheets of raw materials
3. Dangerous Properties of Industrial Materials, 7th Edition, N. Irving Sax and Richard J. Lewis.

PREPARED BY: MORTON PAINT COMPANY
 US Chemical & Plastics
 Alco Industries Companies
 600 Nova Dr SE
 Massillon, OH 44646
 Telephone (330) 830-6000

DATE REVIEWED: April 30, 2007
DATE REVISED: April 30, 2007
REVISION: Section II, III, X

The information in the Material Safety Data Sheet has been compiled from our experience and data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the sheet is the latest one issued.