



## GENERAL INFORMATION

Wax, Grease & Silicone Remover is a solvent blend formulated to dissolve wax, grease, oil, tar, road film, silicone, and other contaminants. Makes an excellent pre-cleaning and pre-painting cleaning solvent.



## 1. COMPONENTS

- 1240 Wax, Grease & Silicone Remover



## 2. MIX RATIO

- Ready-to-use



## 3. POT LIFE

- N/A



## 4. SURFACE PREPARATION

- N/a



## 5. APPLICATION

1. Apply by hand with a soft cloth or spray onto surface and then wipe with a soft cloth.
2. Apply to a two to three square foot area at a time.
3. While the surface is still wet, wipe it dry with a second clean cloth to insure that all contaminants are removed.
4. Repeat steps 1, 2 and 3 as needed.



## 6. TECHNICAL INFORMATION

Color	Clear
Viscosity @ 77°F	Water Thin
Weight Per Full Gallon (Density)	Typical 6.2 lbs/gal
VOC	742 gm/ltr
Flashpoint	Approx. 53°F TCC

\*NOTE: US Regulations allow for the use of exempt compounds for VOC calculations.



## 9. HEALTH & SAFETY

• Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Wear a properly fitting NIOSH/MSHA approved respirator. Select positive pressure supplied respirator (TC-19C or equivalent) for isocyanates. Follow the respirator manufacturer's directions for use. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. USC products are for industrial use by professional, trained painters.